COMMERCIAL WATER HEATERS







Triton Features

Eliminate The Emergency

LeakSense™

Intelligent leak detection system catches leaks as small as a grain of sand and provides real-time alerts that help prevent catastrophic failure.

EcoNet® Smart Monitoring Technology with Integrated Wi-Fi Exclusive technology provides performance updates and alerts via mobile device and full-color LCD display.

Systematic Health Checks
Ongoing self-monitoring of
Triton's most vital components
detects and alerts of potential
issues.

Preventive Maintenance Alerts
Preventive maintenance
reminders to extend the life of
the tank.

Easy Retrofit

Universal Retrofit Across Brands Replace any brand in the market with multiple water connection points and flexible venting options.

Multiple Connection Points
Multiple water connections at the top, side and bottom of the unit simplify installation.

Variety of Flexible Venting Options, Including InnoFlue® Flex Venting

Ideal for replacements and new installs with a selection of the most flexible PVC venting choices, including polypropylene, PVC, CPVC, InnoFlue® Flex Venting and ABS materials; installed in power direct and power vent configurations; can vent 2-, 3-, 4- and 6-inch diameters.

Patented Built-In Condensate Neutralizer

Reduces water acidity for safe drainage at no additional cost.

Built To Last

Triple Pass Heat Exchanger
Constructed with premium
ASME-grade steel to minimize
rust and corrosion for extended
tank life and maximum thermal
efficiency.

Advanced Power Anodes
Self-adjusting, non-sacrificial
power anodes provide
systematic monitoring of anode
health and remaining life on fullcolor LCD unit display.

Longer Useful Life

Triton was designed to last up to 5 years longer than the average commercial water heater.

TRITON COMMERCIAL GAS WATER HEATERS





TRIYON

TRITON HIGH-EFFICENCY COMMERCIAL GAS WATER HEATER

• The most accurate, all-inclusive leak detection and prevention system in the market • LeakSense™ – intelligent leak detection system detects leaks as small as a grain of sand and provides real-time notifications that warn you before catastrophic failure occurs • Systematic Health Checks with Maintenance Alerts - ongoing self-monitoring of Triton's most vital components and alerts of potential issues • Standard built-in Condensate Neutralizer reduces installation time as plumbers no longer need to install this component • Multiple Connection Points - multiple water connections at the top, front and back of the unit simplify installation for replacement of any model • Variety of flexible venting options, including InnoFlue® Flex Venting - polypropylene, PVC, CPVC, InnoFlue® flex vent and ABS materials; venting 2-, 3-, 4- and 6-inch diameters

• Triple Pass Heat Exchanger – constructed with premium ASME-grade steel to minimize rust and corrosion for extended tank life and maximum thermal efficiency • Advanced Power Anodes - self-adjusting, non-sacrificial power anodes provide systematic monitoring of anode health and remaining life • Meets 14ng/J requirement for Ultra-Low NOx • Thermal efficiency 95% to 98% • Additional sizes and configurations available via Special Order with 3- to 5-day delivery
3-YEAR WARRANTY ON TANKS AND 1-YEAR WARRANTY ON PARTS





ITEM NO.	MODEL NO.	GALLON CAPACITY	BTU INPUT	ASME	HEIGHT TO TOP OF VENT	DIAMETER	MINUTES TO RECOVER	APPROX SHIP WEIGHT (LBS.)	GAS CONN. SIZE	DELIVERY
305414720	GHE80SU-130	80	130,000	N	63-5/8"	26-3/8"	31	600	3/4"	DROP SHIP*
305415552	GHE80SU-200	80	199,900	N	63-5/8"	26-3/8"	21	650	3/4"	DROP SHIP*
305418622	GHE100SU-160	100	160,000	N	72-3/4"	26-3/8"	33	725	3/4"	DROP SHIP*
305418790	GHE100SU-200	100	199,900	N	72-3/4"	26-3/8"	26	775	3/4"	STOCKED
305418997	GHE100SU-250	100	250,000	N	72-3/4"	26-3/8"	21	775	3/4"	DROP SHIP*
305419044	GHE100SU-300	100	300,000	N	72-3/4"	26-3/8"	18	775	3/4"	DROP SHIP*
305419080	GHE100SU-400	100	400,000	N	72-3/4"	26-3/8"	13	775	3/4"	DROP SHIP*
305419023	GHE100SU-250A	100	250,000	Υ	72-3/4"	26-3/8"	21	775	3/4"	DROP SHIP*
305419061	GHE100SU-300A	100	300,000	Υ	72-3/4"	26-3/8"	18	775	3/4"	DROP SHIP*
305419095	GHE100SU-400A	100	400,000	Υ	72-3/4"	26-3/8"	13	775	3/4"	DROP SHIP*

COMMERCIAL GAS WATER HEATERS







UNIVERSAL COMMERCIAL GAS WATER HEATER

• The Rheem UniversalTM Series of commercial water heaters are designed for tight retrofit applications • Proprietary steel formulation • Patented multi-flue design and two coats of porcelain enamel result in a superior heat exchanger design • Precision burners and raised port design are formed from high chromium stainless steel • Each burner assembly slides out like a drawer for quick inspection and maintenance • Low-profile damper minimizes overall product height • Heavy-duty vent hood supports help to withstand the rigors of installation • Full-port, full-flow factory-installed brass drain valve allows for faster draining and servicing • 80% thermal efficiency on all heaters • Additional sizes and configurations available via Special Order with 3- to 5-day delivery

3-YEAR WARRANTY ON TANKS AND 1-YEAR WARRANTY ON PARTS



ITEM NO.	MODEL NO.	GALLON CAPACITY	BTU INPUT	ASME	HEIGHT TO TOP OF VENT	DIAMETER	MINUTES TO RECOVER	APPROX SHIP WEIGHT (LBS.)	GAS CONN. SIZE	DELIVERY
304705344	G65-360A	65	360,000	Υ	71"	26-1/4"	11	680	3/4"	DROP SHIP*
304705284	G65-360-1	65	360,000	N	71"	26-1/4"	11	640	3/4"	DROP SHIP*
304686333	G72-250	72	250,000	N	72"	26-1/4"	18	590	3/4"	DROP SHIP*
302727593	G75-125	75	125,000	N	65-1/2"	26-1/4"	37	480	3/4"	STOCKED
304685242	G76-200-1	76	199,900	N	69"	26-1/4"	24	540	3/4"	STOCKED
304684399	G82-156	82	156,000	N	69"	26-1/4"	33	490	3/4"	DROP SHIP*
304685395	G91-200-1	91	199,900	N	77"	26-1/4"	28	600	3/4"	STOCKED
297990	G100-200	100	199,900	N	74"	30-1/4"	31	780	3/4"	STOCKED
304705380	G100-400A	100	399,900	Υ	76"	30-1/4"	15	810	1"	DROP SHIP*

UNIVERSAL COMMERCIAL GAS WATER HEATERS







LOW NOX (LN) UNIVERSAL COMMERCIAL GAS WATER HEATER

- The Rheem Universal™ Series of commercial water heaters are designed for tight retrofit applications
- Proprietary steel formulation Patented multi-flue design and two coats of porcelain enamel result in a superior heat exchanger design • Precision burners and raised port design are formed from high chromium stainless steel • Each burner assembly slides out like a drawer for quick inspection and maintenance
- Low-profile damper minimizes overall product height Heavy-duty vent hood supports help to withstand the rigors of installation • Full-port, full-flow factory-installed brass drain valve allows for faster draining and servicing • 80% thermal efficiency on all heaters • Additional sizes and configurations available via Special Order with 3- to 5-day delivery • Low NOx performance less than 40ng/J
- 3-YEAR WARRANTY ON TANKS AND 1-YEAR WARRANTY ON PARTS



ITEM NO.	MODEL NO.	GALLON CAPACITY	BTU INPUT	ASME	HEIGHT TO TOP OF VENT	DIAMETER	MINUTES TO RECOVER	APPROX SHIP WEIGHT (LBS.)	GAS CONN. SIZE	DELIVERY
311971863	GN65-360A	65	360,000	N	71"	26-1/4"	11	680	3/4"	DROP SHIP*
303837292	GN75-125	75	125,000	N	65-1/2"	26-1/4"	37	480	3/4"	STOCKED
304685580	GN76-200	76	199,900	N	69"	26-1/4"	24	540	3/4"	STOCKED
303837293	GN91-200	91	199,900	N	76-5/16"	26-1/4"	28	600	3/4"	STOCKED
304684290	G100-80N	100	80,000	N	70"	28-1/4"	81	410	1/2"	DROP SHIP*
303837263	GN100-200	100	199,900	N	74"	30-1/4"	31	780	3/4"	STOCKED
304705420	GN100-400A	100	399,900	Υ	76"	30-1/4"	15	810	1"	DROP SHIP*







ULTRA LOW NOX (ULN) UNIVERSAL COMMERCIAL GAS WATER HEATER

- The Rheem Universal™ Series of commercial water heaters are designed for tight retrofit applications
- Proprietary steel formulation
 Patented multi-flue design and two coats of porcelain enamel result in a superior heat exchanger design • Precision burners and raised port design are formed from high chromium stainless steel
- Each burner assembly slides out like a drawer for quick inspection and maintenance Low-profile damper minimizes overall product height • Heavy-duty vent hood supports help to withstand the rigors of installation
- Full-port, full-flow factory-installed brass drain valve allows for faster draining and servicing 80% thermal efficiency on all heaters • Additional sizes and configurations available via Special Order with 3- to 5-day delivery
- Ultra low NOx performance less than 14ng/J **3-YEAR WARRANTY ON TANKS AND 1-YEAR WARRANTY ON PARTS**



ITEM NO.	MODEL NO.	GALLON CAPACITY	BTU INPUT	ASME	HEIGHT TO TOP OF VENT	DIAMETER	MINUTES TO RECOVER	APPROX SHIP WEIGHT (LBS.)	GAS CONN. SIZE	DELIVERY
303837290	G75UN	75	75,000	N	65"	26-1/4"	62	300	1/2"	STOCKED
303837295	GNU75-125	75	125,000	N	65-1/2"	26-1/4"	37	480	3/4"	STOCKED
300308094	GNU76-200	76	199,900	N	69"	26-1/4"	24	540	3/4"	DROP SHIP*
304741063	GNU100-200	100	199,900	N	74"	30-1/4"	31	780	3/4"	STOCKED
311971885	GNU100-270	100	270,000	N	74"	30-1/4"	23	805	3/4"	DROP SHIP*
311971891	GNU100-400	100	399,900	N	76"	40-1/2"	15	770	1"	DROP SHIP*

COMMERCIAL ELECTRIC WATER HEATERS





COMMERCIAL POINT-OF-USE ELECTRIC WATER HEATER

• Designed to eliminate costly temparature loss in long piping runs • Porcelain enamel-lined tank • Heavy-duty anode rod • 2.5-, 6-, 10-, 15-, 20- and 30-gallon capacities • 120V, 208V, 240V, 277V and 480V • 1,400-6,000W

3-YEAR WARRANTY ON TANKS AND 1-YEAR WARRANTY ON PARTS



ITEM NO.	MODEL NO.	GALLON CAPACITY	VOLTS	KW	PHASE	DELIVERY
305030709	EGSP6	6	120	2	1	DROP SHIP*
305030703	EGSP6	6	277	2	1	DROP SHIP*
305030780	EGSP6	6	120	3	1	DROP SHIP*
305030784	EGSP6	6	277	3	1	DROP SHIP*
312272798	EGSP6	6	208	6	1	DROP SHIP*
312272828	EGSP10	10	120	1.5	1	DROP SHIP*
305029847	EGSP10	10	120	2	1	DROP SHIP*
305029796	EGSP10	10	208	2	1	DROP SHIP*
305029891	EGSP10	10	120	3	1	DROP SHIP*
312272787	EGSP10	10	208	3	1	DROP SHIP*
312272806	EGSP10	10	277	3	1	DROP SHIP*
312272992	EGSP10	10	208	6	1	DROP SHIP*
305030444	EGSP15	15	120	2	1	DROP SHIP*
312272998	EGSP15	15	277	3	1	DROP SHIP*
312272985	EGSP20	20	120	1.5	1	DROP SHIP*
305030596	EGSP20	20	120	2	1	DROP SHIP*
305030609	EGSP20	20	120	3	1	DROP SHIP*
305030639	EGSP20	20	208	3	1	DROP SHIP*
305030576	EGSP20	20	277	3	1	DROP SHIP*
312272771	EGSP20	20	208	4.5	1	DROP SHIP*
312273042	EGSP20	20	277	4.5	1	DROP SHIP*
312272780	EGSP20	20	208	6	1	DROP SHIP*
305030564	EGSP20	20	480	6	1	DROP SHIP*

COMMERCIAL ELECTRIC WATER HEATERS





COMMERCIAL ELECTRIC WATER HEATER

• 98% thermal efficiency • Delivers water greater than 170°F • Terminal blocks allow conversion from single-phase to three-phase • Terminal blocks allow simultaneous or non-simultaneous wiring (light-duty only) • Automatic temperature control • 30- to 119.9- gallon capacitites • 208V, 250V, 277V and 480V • 4.5-36KW | Low-lead compliant • Easily convert standard models from simultaneous to non-simultaneous, single-phase to three-phase • Porcelain enamel lined tank • Automatic temperature control • 30 to 119.9-gallon capacitites • 208, 240, 277 and 480 voltages • 4.5-36KW

3-YEAR WARRANTY ON TANKS AND 1-YEAR WARRANTY ON PARTS



ITEM NO.	MODEL NO.	GALLON CAPACITY	VOLTS	KW	PHASE	DELIVERY				
LIGHT-DUTY TERMINAL BLOCK 3-12KW										
305229589	ELDS30-TB	28	208	9 OR 4.5	MULTI	DROP SHIP*				
305229142	ELD40-TB	40	208	9 OR 4.5	MULTI	DROP SHIP*				
305229499	ELDS40-TB	36	208	9 OR 4.5	MULTI	DROP SHIP*				
305229153	ELD40-FTB	40	208	12 OR 6	MULTI	DROP SHIP*				
305229230	ELD52-TB	50	208	9 OR 4.5	MULTI	DROP SHIP*				
305228146	ELDS52-TB	50	208	9 OR 4.5	MULTI	DROP SHIP*				
305229253	ELD52-FTB	50	208	12 OR 6	MULTI	DROP SHIP*				
305228143	ELDS52-FTB	47	208	12 OR 6	MULTI	DROP SHIP*				
305229778	ELD80-FTB	80	208	12 OR 6	MULTI	DROP SHIP*				
LIGHT-DUTY NON-TERMINAL BL	OCK 3-12KW									
312291712	ELD66-C	65	240	4.5	1	DROP SHIP*				
312276935	ELD80-C	80	208	4.5	1	DROP SHIP*				
310000139	ELD80-C	80	240	4.5	1	DROP SHIP*				
HEAVY-DUTY 18-36KW										
305029364	ES85-18-G	85	208	18	3	DROP SHIP*				
312273328	ES120-18-G	120	208	18	3	DROP SHIP*				
312273356	ES120-36-G	120	208	36	3	DROP SHIP*				
312273340	ES120-36-G	120	480	36	3	DROP SHIP*				

